



Catalogue No.	PFP/BL/02		
CHARACTERISTICS	STANDARD VALUE		
LUMINARIES			
Luminaries Wattage	30 Watt		
Input Voltage	230 V		
Input Frequency	50 HZ		
Input Current	0.5 A		
Power Factor	NA		
Athd.	CLASS A		
Efficiency	84%		
Light Spreading Angle	120°		
Temperature Class	T6		
IP Standard	IP66		
Total Weight	6.2 Kg		
Starting Time	Rapid (0.2 Sec)		
Guarantee	2 Years Including FLUX / CCT / CRI		
LED LAMP - Make LUMILEDS			
LED Type / No of LED Lamp	COB / Single Lamp		
Total Lumen @Tc 25°C	3354	3640	4030
Lumen Efficacy (Lm/ Watt)	129 lm/W	140 lm/W	155 lm/W
CCT / Color Rendering index	3000K / RA 70	5000K / RA 70	6500K / RA 80
SP Ratio	2 - 2.25		
MacAdam Ellipse Stage	STEP 3		
LED - Wattage / Current / Voltage	26W / 727ma / 35.8 V		
Lamp Life	1,00,000 Hours Min.		
Certifications / Reports	LM70, Lm80 / Photo Bio. Test / Vibration Test		
Test Report of CREE LED Lamp	Actual Operating test Report for 63,000 Hrs		
LED DRIVER: PHILIPS & FULHAM			
Type of Driver	Constant Current (CC)		
Input Voltage	Range 90 VAC ~ 264 VAC		
Frequency Range	47 ~ 63 Hz		
Inrush Current	COLD START 25A		
Leakage Current	< 0.25 mA / 240 VAC		
Output Protection	Over Voltage		
Withstand Voltage	I/P-0/P:3.75K VAC Min.		
Surge Protection	L-N : 2KV		
OPTICS			
Optics Type	PC		
MOC of Optics	Polycarbonate		
Secondary Optics	Toughened Glass		
FIXTURES / HEAT SINK			
Make Of Fixture	PATCO		
Certification	CMRI Certified including LED Lamp		
MOC Fixtures	Aluminum Casting		
Heat Sink Make	Own Design		
MOC Heat Sink	Aluminum Extrusion LM-06		
Junction Temperature - TJ	68°C		
Case Temperature - TC	55°C		